

VRLA Sealed Rechargeable Batteries

Model	Nominal Voltage (V)	Nominal Capacity (20 hr) (Ah)	L (mm)	Dimensions W (mm)	H Over Terminal (mm)	Weight Approx (Kg)
-------	------------------------	----------------------------------	--------	----------------------	-------------------------	-----------------------

NUMAX - VRLA Battery Range for Standby and Cyclic Use

6 Volt Type						
FNC612	6	1.2	97	25	56	0.37
FNC640	6	4	70	48	106	0.83
FNC670	6	7	151	38	100	1.15
FNC6100	6	10	151	50	100	2.12
FNC6120	6	12	151	95	100	2.17
12 Volt Type						
FNC1212	12	1.2	97	47	56	0.57
FNC1220	12	2	178	34	65	0.83
FNC1230	12	3	134	67	65	1.30
FNC1240	12	4	94	70	105	1.63
FNC1245	12	4.5	94	70	105	1.70
FNC1270	12	7	151	65	100	2.75
FNC1272	12	7.2	151	65	100	2.80
FNC12120	12	12	151	98	100	4.25
FNC12190	12	19	180	75	167	6.50
FNC12210	12	21	192	116	144	7.80
FNC12260	12	26	165	175	126	8.70
FNC12300	12	30	165	125	180	10.50
FNC12340	12	34	196	130	168	11.50
FNC12420	12	42	197	166	174	15.10
FNC12700	12	70	350	166	175	23.70
FNC12800	12	80	342	174	239	33.70
FNC121000H	12	100	342	174	239	35.00
FNC121000S	12	100	443	167	228	40.00
FNC121200	12	120	500	180	225	44.00
FNC121500	12	150	500	260	225	55.00
FNC122000	12	200	500	260	225	68.00

YUASA NP Range - Vented Lead Acid Sealed Rechargeables

NP 1-6	6	1.0	51	42.5	54.5	0.25
NP 1.2-6	6	1.2	97	25	54.5	0.34
NP 2.8-6	6	2.8	134	34	64	0.60
NP 3-6	6	3.0	134	34	64	0.65
NP 4-6	6	4.0	70	47	105.5	0.85
NP 7-6	6	7.0	151	34	97.5	1.35
NP 10-6	6	10.0	151	50	97.5	1.93
NP 12-6	6	12.0	151	50	97.5	2.1
NP 0.8-12	12	0.8	96	25	61.5	0.35
NP 1.2-12	12	1.2	97	48	55	0.57
NP 2-12	12	2.0	150	20	89	0.7
NP 2.1-12	12	2.1	178	34	64	0.9
NP 2.3-12	12	2.3	178	34	64	0.94
NP 2.8-12	12	2.8	134	67	64	1.1
NP 3.2-12	12	3.2	134	67	64	1.17
NP 4-12	12	4	90	70	106	1.70
NP 6-12	12	6.0	151	65	98	2.4
NP 7-12	12	7	151	65	98	2.65
NP 12-12	12	12	151	98	97.5	4
NP 17-12	12	17	181	75	167	6.1
NP 18-12	12	18	180	76	167	6.2
NP 24-12	12	24.0	166	175	125	9
NP 26-12	12	26	166	125	175	9.3
NP 38-12	12	38.0	197	164	170	14.2
NP 65-12	12	65.0	350	166	174	22.8

YUASA NPC Range - For Cyclic Application

NPC 17-12	12	17	181	76	167	6.3
NPC 24-12	12	24	175	166	125	9.0
NPC 38-12	12	38	197	165	170	14.2